

HPH1

MECHANICAL TOOLS CRIMPSTAR® RANGE

for through connectors PE HD insulated, heat shrinkable



Crimpstar®



TECHNICAL FEATURES



Crimping Range

Through connectors PE HD insulated, heat shrinkable.
for conductor sizes 0,5 to 6 sqmm and PA6.6 connectors NL-M, NL-P
for conductor sizes 0,25 to 6 sqmm

Dimensions mm

Length	234,5
Width	73,0
Height	18,3
Weight g	512
Package Dimensions	240 x 81 x 25

Manual tool, compact and easy to use, equipped with:

- treated steel crimp jaws with high mechanical properties.
- factory-set ratchet for crimping control (automatic handle opening upon completion of crimping operation).
- Emergency release lever which, if necessary, opens the crimp jaws before their complete closure.
- Ergonomically designed non-slip moulded plastic grips.

HNKE4

MECHANICAL TOOLS CRIMPSTAR® RANGE

for end sleeves



Crimpstar®



TECHNICAL FEATURES



Crimping Range

End sleeves
for conductor sizes 0,5 to 4 sqmm

Dimensions mm

Length	234,5
Width	73,0
Height	18,3
Weight g	498
Package Dimensions	240 x 81 x 25

Manual tool, compact and easy to use, equipped with:

- treated steel crimp jaws with high mechanical properties.
- factory-set ratchet for crimping control (automatic handle opening upon completion of crimping operation).
- Emergency release lever which, if necessary, opens the crimp jaws before their complete closure.
- Ergonomically designed non-slip moulded plastic grips.